



Each Kit Includes:

- 2 x PVC Coated Flexi Hoses
- 2 x PVC Tape Strips
- 2 x Rubber Washers

Product Features

- Available in the following lengths:
300mm, 500mm and 750mm
- 28mm Bore and stainless steel overbraid
- 1" or 1-1/4" BSP Female or Male Connection
- 19mm wall thickness PVC coated Insulation
- Complies with MIS 3005



Product Information

Made in compliance with MIS 3005 standards, our flexible hoses simplify connecting flow and return pipes to heat pumps and biomass boilers. These hoses dampen vibrations and enable smooth bends during installation. They feature a 28mm inner hose encased in a protective stainless-steel braid.

For easy connection, one end has a male or female BSP thread, while the other uses a 28mm compression fitting. All hoses come pre-insulated with a durable 19mm thick PVC coating that resists weather and UV rays.

Product Code	Product Description
HPFS1285INS	Straight Flexi Hoses 500mm - 28mm x 1" Fem (Pair)
HPFS1287INS	Straight Flexi Hoses 750mm - 28mm x 1" Fem (Pair)
HPFS1145INS	Straight Flexi Hoses 500mm - 28mm x 1.1/4" Fem (Pair)
HPFS1147INS	Straight Flexi Hoses 750mm - 28mm x 1.1/4" Fem (Pair)
HPFA1283INS	Angled Flexi Hoses 300mm - 28mm x 1" Fem (Pair)
HPFA1143INS	Angled Flexi Hoses 300mm - 28mm x 1.1/4" Fem (Pair)
HPFA1285INS	Angled Flexi Hoses 500mm - 28mm x 1" Fem (Pair)
HPFA1287INS	Angled Flexi Hoses 750mm - 28mm x 1" Fem (Pair)
HPFA1145INS	Angled Flexi Hoses 500mm - 28mm x 1.1/4" Fem (Pair)
HPFA1147INS	Angled Flexi Hoses 750mm - 28mm x 1.1/4" Fem (Pr)